

Kona 20

General Purpose Air/Water Hose



Colours available     

Characteristics

Description: General purpose EPDM air/ water hose ideal for everyday use. Flexible and versatile. Abrasion, weather and ozone resistant.

Applications: Air/ water hose used in a wide range of applications such as agriculture, construction, equipment rental, industrial.

Temperature Range: -30°C to +80°C (-30°F to +180°F)

WARNING: Not recommended for steam or fuel. Do not use in environments where oil is present.

Construction

Tube: EPDM rubber. ARPM Class C (limited oil resistance).

Reinforcement: Spiral polyester yarn.

Cover: Smooth black NR/ SBR blend, weather and ozone resistant rubber. ARPM Class C (limited oil resistance).

Packaging: Hose supplied in bulk coils or on plastic reels.

Optional: Private branding, different cover colours, pre-made assemblies.

Technical Specifications: Metric

ID (mm)	OD (mm)	WP (bar)	BP (bar)	BEND RADIUS (mm)	WEIGHT (kg/ mt)
6	13	20	60	50	0.20
8	15	20	60	65	0.25
10	18	20	60	75	0.31
12	21	20	60	100	0.40
16	25	20	60	125	0.52
19	29	20	60	155	0.68
25	37	20	60	205	1.02

For more information please visit our website: www.srhindustries.com