

# Nile 10

Water EPDM Hose



Colours available 

## Characteristics

Description: Professional grade water hose. Remains flexible at low temperatures.

Applications: Premium water hose designed for contractor use.

Temperature Range: -30°C to +80°C (-22°F to +180°F)

**WARNING: Not recommended for steam or fuel. Do not use in environments where oil is present.**

## Construction

Tube: EPDM blend. ARPM Class C (limited oil resistance).

Reinforcement: Spiral polyester yarn.

Cover: Smooth, black, EPDM, weather and ozone resistant rubber.  
ARPM Class C (limited oil resistance).

Packaging: Hose supplied in bulk or as assemblies with brass GHT fittings.

Optional: Private branding, different cover colours, pre-made assemblies.

## Technical Specifications: Imperial

ID (inches)	OD (inches)	WP (PSI)	BP (PSI)	BEND RADIUS (inches)	WEIGHT (lbs / ft)
1/4"	0.51	150	450	2.05	0.10
5/16"	0.59	150	450	2.56	0.12
3/8"	0.67	150	450	3.15	0.14
1/2"	0.75	150	450	4.13	0.15
5/8"	0.91	150	450	5.12	0.21
3/4"	1.02	150	450	5.91	0.25
1"	1.30	150	450	7.87	0.37

For more information please visit our website: [www.srhindustries.com](http://www.srhindustries.com)