# Sirocco 20

## Air Compressor Hose





### Characteristics

**Description**: A sturdy air compressor hose. Weather and ozone resistant. **Applications**: Air compressor hose (Jackhammer hose) used primarily in construction.

Temperature Range: -30°C to +80°C (-22°F to +180°F)

WARNING: Not recommended for steam or fuel. Do not use in environments where oil is present.

#### Construction

Tube: EPDM rubber. ARPM Class C (limited oil resistance).

Reinforcement: Spiral polyester yarn.

Cover: Smooth, black, EPDM, weather and ozone resistant rubber.

ARPM Class C (limited oil resistance).

Packaging: Hose supplied in bulk coils or on plastic reels.

Optional: Private branding, different cover colours, pre-made assemblies.

# Technical Specifications: Imperial

| ID<br>(inches) | OD<br>(inches) | WP<br>(PSI) | BP<br>(PSI) | BEND RADIUS<br>(inches) | WEIGHT<br>(lbs/ft) |
|----------------|----------------|-------------|-------------|-------------------------|--------------------|
| 1/4"           | 0.55           | 300         | 900         | 1.57                    | 0.13               |
| 5/16"          | 0.67           | 300         | 900         | 2.17                    | 0.17               |
| 3/8"           | 0.75           | 300         | 900         | 2.76                    | 0.19               |
| 1/2"           | 0.91           | 300         | 900         | 3.54                    | 0.28               |
| 5/8″           | 1.02           | 300         | 900         | 4.33                    | 0.32               |
| 3/4"           | 1.14           | 300         | 900         | 5.31                    | 0.39               |
| 1″             | 1.46           | 300         | 900         | 6.89                    | 0.59               |